



## SLP-101-8L

### FULL-SIZE PANEL MOUNT KEYBOARD WITH 8 LEVELS OF BACKLIGHTING

iKey's SlimKey™ SLP-101-8L panel mount keyboard provides full-size versatility in a rugged, compact design. It features eight levels of green LED backlighting, and is also available in a night vision (NVIS) compatible configuration. When properly installed, the SlimKey™ SLP-101-8L is engineered for NEMA 4X protection from dust, water and corrosive liquids. It is designed for easy integration into workstations, kiosks and industrial environments. The large numeric pad on the SLP-101-8L allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions. Features: 10-Key Numeric Pad Adjustable backlighting Cleanable, Liquidproof Design Industrial Silicone Rubber Keypad PS/2 or USB configurations available Red Backlit Keys

### Product Code SLP-101-8L

Certifications	NEMA 4X, CE UL 60950, FCC Part 15 Class B
Shock	3 X 11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10' straight (3 m) DESIGN: "Y" PS/2 or USB Cable
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
Vibration	Vibration POWER SPECTRAL DENSITY: .04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port)
Compatibility	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
Warranty	1 Year Limited Warranty
Humidity	100% Humidity Resistant
Dimensions	15.10" x 6.05" x 0.58" (w-h-d) 383.5mm x 153.7mm x 14.7mm SCREWS: 0.50" (12.7mm) CUTOUT: 13.70" x 4.65" (w-h) 348mm x 118.1mm
Model Number	SLP-101-PS2: With PS/2 cable SLP-101-USB: With USB cable